

Urethane Timing Belt - Vulcanizer



Simple Setup - Easy To Use - Excellent Splice

Features & Benefits

- **Small & Compact Size**
Unit Dimensions: 7" x 6" x 11.5" tall
- **Light Weight: 12.8 lbs.**
- **Electric 120V**
- **Fast Cycle Time**
- **Air Cooled**
- **High Quality Construction**
- **Belt Widths - Max. 2" wide**
- **Tooth Pitch Matrix, Made to Specifications**
- **Available Belt Pitches - Inch & Metric**



Patent Pending

F.N. SHEPPARD & CO.
Belting Specialties

www.fnsheppard.com 800-733-5773

1261 Jamike Dr., Erlanger, KY
428 Zimmer Rd., Ft. Mill, SC
61 Quaker Oats Dr., Jackson, TN
10101 Bunsen Way, Louisville, KY
4070 St. Hwy., Oshkosh, WI
Sales Offices: Woodbury, NJ
Cobourg, ON, Canada

859-525-2358 • Fax 859-525-8467
803-547-2358 • Fax 803-548-6618
731-427-7440 • Fax 731-423-3013
502-499-8599 • Fax 502-499-7330
920-233-7070 • Fax 920-233-7202
859-653-3857
289-252-0593