



Minimum Pulley Diameter	Belt Thickness																
	Up to .047" or 3/64"	.063" 1/16"	.093" 3/32"	.125" 1/8"	.156" 5/32"	.187" 3/16"	.219" 7/32"	.25" 1/4"	.281" 9/32"	.313" 5/16"	.375" 11/32"	.406" 25/64"	.438" 7/16"	.500" 1/2"	.563" 9/16"	.625" 5/8"	.688" 11/16"
	Up to 1.2mm	1.6mm	2.4mm	3.2mm	4.0mm	4.8mm	5.6mm	6.4mm	7.1mm	7.9mm	9.0mm	10.0mm	11.1mm	12.7mm	14mm	16mm	17mm
4" 102mm					4-2												
						4 1/2-3											
						25											
							RS187										
5" 127mm								4									
								U4									
									4 1/2								
6" 152mm										5							
										U5							
7" 175mm											6						
											U6						
6"/152mm												35					
													7				
9"/225mm																	
12"/305mm																	
14"/356mm																	
18"/450mm																	
Minimum Pulley Diameter	Up to .047" or 3/64"	.063" 1/16"	.093" 3/32"	.125" 1/8"	.156" 5/32"	.187" 3/16"	.219" 7/32"	.25" 1/4"	.281" 9/32"	.313" 5/16"	.375" 11/32"	.406" 25/64"	.438" 7/16"	.500" 1/2"	.563" 9/16"	.625" 5/8"	.688" 11/16"
	Up to 1.2mm	1.6mm	2.4mm	3.2mm	4.0mm	4.8mm	5.6mm	6.4mm	7.1mm	7.9mm	9.0mm	10.0mm	11.1mm	12.7mm	14mm	16mm	17mm

Clipper	Unibar	Alligator	Staple	Bolt Hinged	Rivet Hinged	Bolt Solid Plate
---------	--------	-----------	--------	-------------	--------------	------------------